



HOREPOS
More than POS solutions **HP-260N**

Velocidad de impresión: 260mm/s
Interfaz: USB + SERIE + LAN
Papel 80mm
*Disponible en color blanco y negro



HOREPOS
More than POS solutions **HP-200WF**

Velocidad de impresión: 200mm/s
Interfaz: USB + SERIE + LAN + WIFI
Papel 80 mm



HOREPOS
More than POS solutions **HP-265K**

Velocidad de impresión: 260mm/s
Interfaz: USB + SERIE + LAN
Papel 80mm



HOREPOS
More than POS solutions **HP-330**

Velocidad de impresión 300mm/s
Interfaz: USB + SERIE + LAN
Papel 80mm
*Disponible en color blanco y negro



HOREPOS
More than POS solutions **HP-810P**

Velocidad de impresión 70mm/s
Interfaz: USB + BT / USB + WIFI + BT
Papel 50mm
* Impresora portátil. Funda Incluida

ESPECIFICACIONES

	Model	HP-260N	HP-200WF	HP-265K	HP-330	HP810P
	RAM	8MB	8MB	8MB	8MB	8MB
	FLASH	4MB	8MB	8MB	8MB	8MB
Network	with wire	x		x	x	
	wireless		x			x
Printing	Printing Method	Thermal direct	Thermal direct	Thermal direct	Thermal direct	Thermal direct
	Printing Width	72mm	72mm	72mm	72mm	203dpi
	Resolution	203dpi	203dpi	203dpi	203dpi	203dpi
	Printing Speed	260mm/s	200mm/s	260mm/s	330mm/s	70mm/s
	Paper Width	80mmMAX	80mmMAX	80mmMAX	80mmMAX	80mmMAX
	Paper Compartment Capacity	80mmMAX	80mmMAX	80mmMAX	80mmMAX	80mmMAX
Cutting	Cutter	support& lifespan 2 million cut				
	Tear bar	support				
Outside interface	Cash drawer	1*RJ11				
		ethernet/Serial/USB				
Key	Power Key/Cover Key/Feed Key/DIP Switch					
Light		3PCS				
Voice	buzzer	support				
	suona	Voice alarm				
Power	Adapter	24V2.5A				
Compatibility	Supported system	XP,Win7,Win8,Win10,ios, Android, Linux , MacOS				
Language	Display language	Support most languages, individual language to be customized				
	Printing language	Support most languages, individual language to be customized				
Packaging/accessories	USB Cable - power cord- Adapter - Serial Cable - quick installation guide					
Packaging	■ kraft ■ Pearl cotton paper tray					
Environment	temperature	Storage temperature : -10°C—60°C /working temperature : 0°C—45°C				
	humidity	Storage humidity : 10%—95% / working humidity : 20%—90%				

DISTRIBUIDOR AUTORIZADO