



**TP-1617**

S.O. Android

**TP-2617**

Procesador 3965U

**TP-3617**

Procesador i3



Periféricos Modulares



Configuración del Montaje



Diseño Ergonómico

# TP-1617 / TP-2617 / TP-3617

## ESPECIFICACIONES



	Motherboard	TP-1617	TP-2617	TP-3617	
System	Processor	Qualcomm® 450	Intel Kaby Lake Celeron 3965U	Intel® i3-7100U	
	Memory	3GB LPDDR3	4GB DDR4	8GB DDR4	
	Storage	32GB Emmc	128Gb SSD	128GB SSD	
	Supported OS	Android 9.0	Windows 10	Windows 10	
I/O Ports	Front Side				
	USB	1x USB2.0			
	Power Button	1			
	Rear Side				
	USB	1x USB3.0 (Type C) 1x Micro USB 2x USB3.0 2x USB2.0	2x USB3.0 (Type C) 2x USB3.0 2x USB2.0		
	Serial Port	2x DB9 (Powered RS232) (default 0V; COM1 5V, COM2 12V)			
	LAN	1x RJ45			
	Cash Drawer	1x RJ11			
	FeDP	2x miniDP			
	DC Jack	1x 4PIN DIN (with latch)			
Display	Size and Resolution	15.6" 1920 x 1080 (16:9)			
	Touch Screen	True-Flat PCAP multi-touch			
Power	Power Adapter	65W / 19V	120W / 19V		
Certificate	EMC & Safety	FCC Class A, CE Mark, LVD			
Environment	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)			
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)			
	Humidity	20% ~ 85% RH non-condensing			
Dimensions (WxDxH)	369 x 200 x 375 mm (14.5" x 7.9" x 14.8")				
Options	Wireless LAN + BT	BT4.1 WiFi 802.11 b/g/n/ac		M.2(E-Key) WiFi/BT Module	
	Speaker	1 x 3W			
	MSR	3-Track MSR			
	Fingerprint	Fingerprint Reader			
	NFC	NFC Reader			
	iButton	iButton			
	Scanner	2D Scanner			
	Customer Display	LCM display 2 x 20 characters			
	2nd Display	11.6" & 15.6" 2nd display			
	Cable	Converter cable for FeDP to VGA			
	Thermal Solution	N/A		Heatsink kit	

**DISTRIBUIDOR AUTORIZADO**