

TP-1590D



Pantalla plana
sin bisel de 15 "
con PCAP Touch



Cuerpo elegante
y compacto
de tamaño reducido



VFD y
segunda pantalla
opcional

TP-1590D

ESPECIFICACIONES

Specification	
CPU	Intel® Celeron® J1900(2.0 GHz, 4 Cores). Fanless
System Memory	4GB Standard, 1 x SOOIMM (Max. 8GB)
Storage (M.2 M key size 2242)	55D 64GB, (Max 256GB)
Display	15" TFT LCD, LEO Backlight
Touch Screen	PCT(Projected Capacitive Touch)
Operation System	Windows 7/8/10
External I/O Options	
LAN port(10/100/1000 Mbps)	PCI-E LAN 1000Mbps Ethernet
VGA	1 x VGA (With Power Output)
USB port	4(USB 3.0 x 1, USB 2.0 x 3)
COM port	COM x1 R5232
Audio	1 x Line-out
Keyboard	Keyboard
Parallel	LPT x 1
Power	
Power Supply	Adaptar 24V, 2A
Operating Temperature	0 °C - 60 °C at 10% to 90% Humidity
Storage Temperature	20 °C - 80 °C at 10% to 90% Humidity
Dimensions (W x H x O)	364 x 333 x 210 (mm)
NetWeight	5,000g
Peripheral Options	
I/O Expansion	1 x Cash Drawer Port (Factory Dption) 1 x Powered USB (24V)
Customer Display	VFD, 20 Columns x 2 Lines
Storage	55D 128GB, HDD 500GB, 1TB
WiFi	Mini PCIe for Wireless LAN
Serial Conversion Cable	RJ-45 to O-sub 9 2 x 0.8W (Stereo)

DISTRIBUIDOR AUTORIZADO