



TP- 650



Display modular  
20 columnas  
x 2 líneas



Impresora de tickets  
térmica  
integrada en la base



Display secundario  
LCD  
10.4"

# TP-650

# ESPECIFICACIONES

Model	POP-650-B
<b>Main Board</b>	
CPU	Intel® Bay Trail-D Platform, Celeron® Processor J1900 (2.0 GHz, 2M Cache)
System Memory	1 x DDR3L SO-DIMM 1333MHz, up to 8 GB
Graphic Memory	Intel® HD Graphics
OS Support	POS Ready 7, Linux, Windows 7
<b>Display</b>	
Screen Size	15" Full Flat LCD Monitor
Brightness	300 nits
Resolution	1024 x 768 Pixel
Touch Screen	5 Wire Resistive Type or Projective Capacitive
Tilting Angle	35 ~ 90 Degree
<b>Storage</b>	
HDD	1 x 2.5" SATA
Compact Flash	1 x CFast Slot for SATA I / SATA II
<b>Interface</b>	
Serial	4 x COM (DB9, with COM 1/COM 2 power output, +5VDC/+12VDC, selectable by Jumper)
USB	1 x USB 3.0 (External), 4 x USB 2.0 (External, 2 x bottom/ 2 x side)
PS/2 Mouse	1 x PS/2 (for PS/2 Keyboard/Mouse)
PS/2 Key Board	
LAN	1 x RJ-45, Giga LAN Support
VGA	1 x DB-15, Female
DC Out	1 x 12VDC Jack for Customer Display or 2nd Display, 1 x 24VDC 3-pin Connector with Lock for Printer
Cash Drawer	1 x RJ-11, +12/+24 VDC
Audio Jack	1 x Line Out, 1 x MIC In, 1 x Internal Speaker 2W
<b>Others</b>	
Power Input	12VDC 180W, 4-pin Connector with Lock (External Adaptor: 100~240 VAC, 50/60HZ)
Color	Silver, Black
Compliance	FCC / CE / WEEE / RoHS
Weight	8.5 Kg
Dimension (W x D x H: mm)	391(W) x 266(D) x 395(H)
Operating Temperature	0°C~40°C
Operating Humidity	20%~80% RH non-condensing
Storage Temperature	-20°C~55°C
Storage Humidity	20%~85% RH non-condensing

DISTRIBUIDOR AUTORIZADO