

**TP- 8515**



Pantalla LCD  
secundaria  
opcional



Periféricos modulares:  
MSR, i-Button, RFID,  
Finger Print, etc.



Diseño  
y  
Durabilidad

# TP-8515

## ESPECIFICACIONES



Model	TP-8515
<b>Main Board</b>	
CPU	Intel® Bay Trail-D Platform, Celeron® Processor J1900 2.0 GHz (2M Cache, up to 2.42 GHz)
System Memory	1 x DDR3L SO-DIMM Socket, up to 8GB
Graphic	Intel® HD Graphics
OS Support	POS Ready 7, Windows 7, Windows 8.1, Windows 10 IOT Entry, Linux
<b>Display</b>	
Screen Size	15" TFT LCD LED backlight, (Ratio 4:3)
Resolution	1024 x 768
Touch Screen	Projective Capacitive Touch, 10 point
Tilting Angle	90~180 degree
<b>Storage</b>	
HDD	1 x 2.5" SATA II Bay HDD or SSD
<b>Interface</b>	
Serial	4 x COM (3 for standard, 1 for optional, DB9 with RI/+5VDC/+12VDC output by jumper)
Parallel	1 x DB25 Parallel Port (optional)
USB	5 x USB 2.0 (External, 4 x Bottom, 1 x Screen)
PCIe	1 x Mini PCIe
LAN	1 x RJ-45, Giga LAN Support (10/100/1000 Mbps)
VGA	1 x DB-15, Female (Max Resolution: 1920 x 1080)
DC Out	1 x +12VDC for 2nd Display / VFD
DC In	1 x +12VDC
Cash Drawer	1 x RJ-11, +12VDC/+24VDC by jumper select
Audio	1 x Line in and 1 x Mic. out
<b>Others</b>	
Power Adaptor	+12V/5A, 60W External Power Adaptor with Cable Head Lock, secured in POS Unit (Power Adaptor: 100VAC~240VAC, 50/60Hz)
Color	Black / White
Compliance	FCC/CE/WEEE/RoHS
Weight	6 kg
Dimension (mm)	364 (W) x 379 (H) x 236 (D)
Operating Temperature	0°C~40°C
Operating Humidity	20% ~ 80% RH non-condensing
Storage Temperature	-20°C~55°C
Storage Humidity	20% ~ 85% RH non-condensing

DISTRIBUIDOR AUTORIZADO