



i3



Periféricos integrados:
lector de tarjetas,
lector códigos QR...



Display secundario
LCD
7"



Ajustable a todos
los ángulos de visión
hasta 60°



i-3

ESPECIFICACIONES

Specification	i3			
CPU	Intel® Celeron J1900 Quad Core 2.0 GHz			
System Memory	SO-DIMM DDR3L*1 up to 8GB			
Storage (M.2 M key size 2242)	internal pre-installed 2* M.2 SATA SSD (32GB up to 512GB each socket)			
Display	15" LED backlight TFT LCD, 1024*768, 250 or 350 cd/m ²			
Touch Screen	PCT(Projected Capacitive Touch)			
Operation System	Win 7, POSReady 7, Win 10 IoT 64 bit			
External I/O Options	I	II	III	IV
LAN port(10/100/1000 Mbps)	1			
VGA	1	N/A	1	N/A
USB port	4*USB 2.0			
Serial port	2*DB-9,1*RJ48	3*DB-9,1*RJ48	2*DB-9	3*DB-9
Cash Drawer (24V)	N/A	N/A	1	1
Others	2*Built-in Speakers (options), 1*audio			
GTP-182 Thermal Printer	Dot Density: 8 dot/mm / Printing Speed Maximum 250mm/s Paper Roll width: 80mm / Interface: USB 2.0			
Mechanical & Environment				
Dimensions & Weight				
Safety Certifications & IP Rating	FCC/CE, IP 54 Compliance			
Storage & Operating Temp.	-20°C ~ 60°C, 0°C ~ 40°C			
Relative Humidity	10% ~ 90% (non-condensing)			
Power Consumption	120W maximum			
Peripheral Options				
Wireless communication	802.11 b/g/n/ac Wireless LAN (M.2 E key size 2230) 3G/4G LTE (M.2 B key size 3042)			
Customer Display	SENOR AMON 10 or 15 Series / VFD 20*2lines Display 7" LCD integrated type with PCT touch			
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks			
Smart Card Reader	ISO-7816 compatible			
Identification Devices (choose 1)	RFID (ISO/IEC 14443A / 13.56 MHz / Mifare S50)			
Identification Devices (choose 1)	Fingerprint Reader or i-Button			

DISTRIBUIDOR AUTORIZADO