

# KIOSK

## About Self-Service Kiosk Series

To enhance the growth and efficiency of your business and ensuring an excellent guest experience, Self-Service Kiosk Series help you make placing customer orders easier than ever.



### Features

- Modular design, easy to maintain
- Integration with wide variety of peripherals and devices
- Provide flexibility to add future components and upgrades
- Custom modifications to the color, shape and finish

### Applications

- Retail and chain stores
- Café and restaurants
- Airport and hotel check-in
- Movie theater and entertainment center

**FAMETECH INC.**  
Your Reliable POS Solution Provider



TYSSO



## About Fametech Inc.

Founded in 1981, the company grew with a strong R&D background and the whole team is committed to staying at the leading edge of the Auto-ID and POS technology sphere.



**TYSSO FAMETECH INC.**

Headquarter: 12F-8, No.237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

TEL: 886-2-86922060  
FAX: 886-2-86922061  
www.fametechn.com.tw  
info@fametechn.com.tw



We are offering one-stop POS solutions to deliver your best customer experience and providing full-range product lines that cover most POS applications including POS Terminals, Barcode Scanners, Receipt Printers, Barcode Label Printers, Magnetic Stripe Card Readers, Customer Displays, Touch Screen Monitors, and many other POS peripheral devices.

# 21.5-inch KIOSK

KS-3X21 (Series)



# 27-inch KIOSK

KS-5X27 (Series)



# 32-inch KIOSK

KS-1X32 (Series)



## KIOSK Comparison Sheet

Model	KS-3121	KS-3821	KS-5527	KS-5827	KS-1132	KS-1532	KS-1832		
<b>Configuration</b>									
Mainboard	Processor	ARM Rockchip RK3288 Quad-core Cortex-A17 up to 1.8GHz	Intel® Core™ i3 7100U (3M Cache, 2.40 GHz) Intel® Core™ i5 7200U (3M Cache, up to 3.1 GHz)	Intel® Bay Trail-D Celeron® J1900 Quad Core (2M Cache, up to 2.42 GHz)	Intel® Core™ i3 7100U (3M Cache, 2.40 GHz) Intel® Core™ i5 7200U (3M Cache, up to 3.1 GHz)	ARM Rockchip RK3288 Quad-core Cortex-A17 up to 1.8GHz	Intel® Bay Trail-D Celeron® J1900 Quad Core (2M Cache, up to 2.42 GHz)	Intel® Core™ i3 7100U (3M Cache, 2.40 GHz) Intel® Core™ i5 7200U (3M Cache, up to 3.1 GHz)	
	Memory	2GB DDR3 1333	up to 32G DD4 SO-DIMM	up to 8G DDR3L	up to 32G DD4 SO-DIMM	2GB DDR3 1333	up to 8G DDR3L	up to 32G DD4 SO-DIMM	
	Storage	16GB eMMC (up to 32G) + 1 x Micro SD (up to 128GB)	1 x M.2 SATA Slot	1 x M.2 SATA Slot	1 x M.2 SATA Slot	16GB eMMC (up to 32G) + 1 x Micro SD (up to 128GB)	1 x M.2 SATA Slot	1 x M.2 SATA Slot	1 x M.2 SATA Slot
LCD Panel	Panel Size	21.5-inch VA LED Panel	21.5-inch VA LED Panel	27-inch VA LED Panel	27-inch VA LED Panel	32-inch IPS LED Panel	32-inch IPS LED Panel	32-inch IPS LED Panel	
	Resolution	1080 (V) x 1920 (H)	1080 (V) x 1920 (H)	1080 (V) x 1920 (H)	1080 (V) x 1920 (H)	1080 (V) x 1920 (H)	1080 (V) x 1920 (H)	1080 (V) x 1920 (H)	
	Brightness	250nits	250nits	300nits	300nits	400nits	400nits	400nits	
	View Angle	89° / 89° / 89° / 89°	89° / 89° / 89° / 89°	89° / 89° / 89° / 89°	89° / 89° / 89° / 89°	89° / 89° / 89° / 89°	89° / 89° / 89° / 89°	89° / 89° / 89° / 89°	
Touch Panel	Bezel Free	True-Flat PCAP Touch (G+G)	True-Flat PCAP Touch (G+G)	True-Flat PCAP Touch (G+G)	True-Flat PCAP Touch (G+G)	True-Flat PCAP Touch (G+G)	True-Flat PCAP Touch (G+G)	True-Flat PCAP Touch (G+G)	
Audio	Internal Speaker	2 x 5W Speakers	2 x 5W Speakers	2 x 5W Speakers	2 x 5W Speakers	2 x 5W Speakers	2 x 5W Speakers	2 x 5W Speakers	
<b>In Front Control</b>									
External I/O Interface	USB	2 x USB 2.0 type A	2 x USB 2.0 type A	2 x USB 2.0 type A	2 x USB 2.0 type A	2 x USB 2.0 type A	2 x USB 2.0 type A	2 x USB 2.0 type A	
	LAN	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	
	Power Cord Socket	1 x AC Male Power Socket	1 x AC Male Power Socket	1 x AC Male Power Socket	1 x AC Male Power Socket	1 x AC Male Power Socket	1 x AC Male Power Socket	1 x AC Male Power Socket	
	Power Button	1 x Power Switch Button	1 x Power Switch Button	1 x Power Switch Button	1 x Power Switch Button	1 x Power Switch Button	1 x Power Switch Button	1 x Power Switch Button	
<b>Mechanical &amp; Environmental</b>									
Physical Characteristics	Mounting Style	Floor Standing or Wall Mounting	Floor Standing or Wall Mounting	Floor Standing or Wall Mounting	Floor Standing or Wall Mounting	Floor Standing or Wall Mounting	Floor Standing or Wall Mounting	Floor Standing or Wall Mounting	
	Housing Color Plan	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	
	Brand Logo	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	Standard or Customizable by project	
	Dimension	Main System : 345 (W) x 897 (H) x 170 (D) mm With Stand : 500 (W) x 1700 (H) x 480 (D) mm	Main System : 345 (W) x 897 (H) x 170 (D) mm With Stand : 500 (W) x 1700 (H) x 480 (D) mm	Main System : 420 (W) x 945 (H) x 110 (D) mm With Stand : 600 (W) x 1700 (H) x 400 (D) mm	Main System : 420 (W) x 945 (H) x 110 (D) mm With Stand : 600 (W) x 1700 (H) x 400 (D) mm	Main System : 509 (W) x 1100 (H) x 144 (D) mm With Stand : 609 (W) x 1750 (H) x 576 (D) mm	Main System : 509 (W) x 1100 (H) x 144 (D) mm With Stand : 609 (W) x 1750 (H) x 576 (D) mm	Main System : 509 (W) x 1100 (H) x 144 (D) mm With Stand : 609 (W) x 1750 (H) x 576 (D) mm	Main System : 509 (W) x 1100 (H) x 144 (D) mm With Stand : 609 (W) x 1750 (H) x 576 (D) mm
	Weight	13KG (Main System Only) and 25KG (with Stand)	13KG (Main System Only) and 25KG (with Stand)	17KG (Main System Only) and 28KG (with Stand)	17KG (Main System Only) and 28KG (with Stand)	47KG (Main System Only) and 46KG (with Stand)	47KG (Main System Only) and 46KG (with Stand)	47KG (Main System Only) and 46KG (with Stand)	47KG (Main System Only) and 46KG (with Stand)
Operation System	OS	Android 7.1	Windows 10.1 IoT Ent	Win 7/POSReady 7/WE 8.1 IndustryWin 10 IoT Ent	Windows 10.1 IoT Ent	Android 7.1	Win 7/POSReady 7/WE 8.1 IndustryWin 10 IoT Ent	Windows 10.1 IoT Ent	
Environment	Operation Condition	0°C to +35°C / 20 to 80% without condensation	0°C to +35°C / 20 to 80% without condensation	0°C to +35°C / 20 to 80% without condensation	0°C to +35°C / 20 to 80% without condensation	0°C to +35°C / 20 to 80% without condensation	0°C to +35°C / 20 to 80% without condensation	0°C to +35°C / 20 to 80% without condensation	
	Storage Condition	-5°C to +55°C / 20 to 85% without condensation	-5°C to +55°C / 20 to 85% without condensation	-5°C to +55°C / 20 to 85% without condensation	-5°C to +55°C / 20 to 85% without condensation	-5°C to +55°C / 20 to 85% without condensation	-5°C to +55°C / 20 to 85% without condensation	-5°C to +55°C / 20 to 85% without condensation	
<b>Optional Accessories</b>									
Thermal Printer	2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported	2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported	2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported	2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported	2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported	2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported	2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported	2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported	
QR Code Scanner	Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen	Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen	Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen	Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen	Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen	Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen	Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen	Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen	
Face Camera	2M-Pixel Full HD Camera	2M-Pixel Full HD Camera	5M-Pixel AF Full HD Camera	5M-Pixel AF Full HD Camera	2M-Pixel Full HD Camera	2M-Pixel Full HD Camera	2M-Pixel Full HD Camera	2M-Pixel Full HD Camera	
MSR/IC Card Reader	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	
Payment Mount Bracket	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	Based on customer requirements	
More Optional	Wi-Fi IEEE 802.11 a/b/g/n Indoor wheels (under floor stand)	Wi-Fi IEEE 802.11 a/b/g/n/ac ( M.2 type) 3G/4G Module (Mini-PCIe type) Indoor wheels (under floor stand)	Wi-Fi IEEE 802.11 a/b/g/n/ac (Mini-PCIe type) or 3G/4G Module (Mini-PCIe type) Indoor wheels (under floor stand)	Wi-Fi IEEE 802.11 a/b/g/n/ac ( M.2 type) 3G/4G Module (Mini-PCIe type) Indoor wheels (under floor stand)	Wi-Fi IEEE 802.11 a/b/g/n/ac ( M.2 type) 3G/4G Module (Mini-PCIe type) Indoor wheels (under floor stand)	Wi-Fi IEEE 802.11 a/b/g/n/ac (Mini-PCIe type) or 3G/4G Module (Mini-PCIe type) Indoor wheels (under floor stand)	Wi-Fi IEEE 802.11 a/b/g/n/ac ( M.2 type) 3G/4G Module (Mini-PCIe type) Indoor wheels (under floor stand)	Wi-Fi IEEE 802.11 a/b/g/n/ac ( M.2 type) 3G/4G Module (Mini-PCIe type) Indoor wheels (under floor stand)	

## Flexible Customization for Your Business

Optional accessories, customizable color and logo optional supported

### Color



## KS Series Customized

<p><b>Architecture</b> x86  ARM</p>	<p><b>Operating System</b> Windows  Android</p>	<p><b>Processor</b> Intel® Bay Trail J1900 Intel® Kaby Lake Core-i  Rockchip</p>
<p><b>Panel Size</b> 21.5" / 27" / 32"</p>	<p><b>Payment Device</b> QR Code Scanner Contact Card Reader Contactless Card Reader Customized Device Bracket</p>	<p><b>Connection</b> Wi-Fi 3G/4G (x86 only)</p>
<p><b>Thermal Printer</b> 2" Thermal Printer 3" Thermal Printer</p>	<p><b>Face Camera</b> 2M FF Face Camera 5M AF Face Camera</p>	<p><b>Base (Floor Stand)</b> With Indoor Wheels Without Indoor Wheels</p>
<p><b>Wall Mount Bracket</b></p>	<p><b>Customized Logo</b></p>	<p><b>Table Number Plate</b></p>
<p><b>Self-Take Meal Pager</b></p>		

The information includes specification, optional accessories, and customizable menu in this brochure is for reference purposes only. Farnatech Inc. reserves the right to update and change at any time without notice. All information is subject to the actual shipment in each region.