

KS-5527



Quiosco de autoservicio montable



Integración de dispositivos basada en las necesidades del cliente



Personaliza la apariencia, el diseño y los periféricos integrados de su Quiosco

KIOSKO KS-5527

ESPECIFICACIONES

Model		KS-5527
Configuration		
Mainboard	Processor	Intel® Bay Trail-D Celeron® J1900 Quad Core (2M Cache, up to 2.42 GHz)
	Memory	up to 8G DDR3L
	Storage	1 x M.2 SATA Slot
LCD Panel	Panel Size	27-inch VA LED Panel
	Resolution	1080 (V) x 1920 (H)
	Brightness	300nits
	View Angle	89° / 89° / 89° / 89°
Touch Panel	Bezel Free	True-Flat PCAP Touch (G+G)
Audio	Internal Speaker	2 x 5W Speakers
In Front Control		
External I/O Interface	USB	2 x USB 2.0 type A
	LAN	2 x Gigabit Ethernet
	Power Cord Socket	1 x AC Male Power Socket
	Power Button	1 x Power Switch Button
Mechanical & Environmental		
Physical Characteristics	Mounting Style	Floor Standing or Wall Mounting
	Housing Color Plan	Standard or Customizable by project
	Brand Logo	Standard or Customizable by project
	Dimension	Main System : 420 (W) x 945 (H) x 110 (D) mm With Stand : 600 (W) x 1700 (H) x 400 (D) mm
	Weight	17KG (Main System only) and 28KG (with Stand)
Operation System	OS	Win 7/POSReady 7/WE 8.1 Industry/Win 10 IoT Ent
Environment	Operation Condition	0°C to +35°C / 20 to 80% without condensation
	Storage Condition	-5°C to +55°C / 20 to 85% without condensation
Optional Accessories		
Thermal Printer		2" or 3" standalone thermal printer with cutter 203 dpi and 200 mm/s supported
QR Code Scanner		Fixed mount barcode scanner, 752 x 480 CMOS Optimized to read barcode from a mobile phone screen
Face Camera		5M-Pixel AF Full HD Camera
MSR/IC Card Reader		Based on customer requirements
Payment Mount Bracket		Based on customer requirements
More Optional		Wi-Fi IEEE 802.11 a/b/g/n/ac (Mini-PCIe type) or 3G/4G Module (Mini-PCIe type) Indoor wheels (under floor stand)

DISTRIBUIDOR AUTORIZADO