

Modular POS System **TP-1515**



Features



Full Flat Touch Screen



MSR Module



Rear Mount VFD Display



10.4" Second LCD Display



Sleek & Compact Design



Side Photo

Specifications

Model		TP-1515
Main Board		
CPU	Intel® Bay Trail-D Platform, Celeron® Processor J1900 2.0 GHz (2M Cache, up to 2.42 GHz)	
System Memory	1 x 204-pin DDR3L 1333 SO-DIMM Socket, up to 8GB	
Graphic	Intel® HD Graphics	
OS Support	POS Ready 7, Windows 7, Windows 8.1, Windows 10 IOT Entry, Linux	
Display		
Screen Size	15" TFT LCD LED backlight, (Ratio 4:3)	
Resolution	1024 x 768	
Touch Screen	Projective Capacitive Touch / 5-Wire Resistive Touch	
View Angle	80 degree	
Storage		
HDD	1 x 2.5" SATA II Bay HDD or SSD	
Interface		
Serial	3 x COM (COM1 &2 support RI/+5VDC/+12VDC output by jumper, COM3 support RI/+3.3V/+5V by jumper)	
Parallel	1 x DB25 Parallel Port (optional)	
USB	4 USB type A(3 x USB 2.0 & 1 x USB 3.0)	
LAN	1 x RJ-45, Giga LAN Support (10/100/1000 Mbps)	
VGA	1 x DB-15, Female (Max Resolution: 1920 x 1080)	
DC Out	1 x +12VDC for 2nd Display / VFD	
DC In	1 x +12VDC	
Cash Drawer	1 x RJ-11, +12VDC/+24VDC by jumper select	
Audio	1 x Line in and 1 x Mic. out	
Others		
Power Adaptor	+12V/5A, 60W External Power Adaptor with Cable Head Lock, secured in POS Unit (Power Adaptor: 100VAC~240VAC, 50/60Hz)	
Color	Black	
Compliance	FCC/CE/RoHS	
Weight	5 kg	
Dimension (mm)	364 (W) x 379 (H) x 236 (D)	
Operating Temperature	0°C~40°C	
Operating Humidity	20% ~ 80% RH non-condensing	
Storage Temperature	-20°C~55°C	
Storage Humidity	20% ~ 85% RH non-condensing	